

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 10716-2 (1999): Technical Product Documentation - Springs, Part 2: Presentation of Data for Cylindrical Helical Compression Springs [PGD 24: Drawings]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS 10716 (Part 2) : 1999
ISO 2162-2 : 1993

भारतीय मानक

तकनीकी उत्पाद प्रलेखन — स्प्रिंग

भाग 2 बेलनाकार सर्पिल संपीडक स्प्रिंग के लिए आँकड़ा प्रस्तुतीकरण

Indian Standard

TECHNICAL PRODUCT DOCUMENTATION — SPRINGS

PART 2 PRESENTATION OF DATA FOR CYLINDRICAL HELICAL COMPRESSION SPRINGS

ICS 01.100.20; 21.160

© BIS 1999

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

August 1999

Price Group 4

NATIONAL FOREWORD

This Indian Standard (Part 2) which is identical with ISO 2162-2 : 1993 'Technical product documentation — Springs — Part 2 : Presentation of data for cylindrical helical compression springs' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendation of Drawings Sectional Committee and approval of Light Mechanical Engineering Division Council.

This standard was originally published in 1983 by adopting ISO 2162 : 1973 'Technical drawings — Representation of springs'. ISO 2162 has since been revised in 1993 by splitting it into the following three parts, under the general title 'Technical product documentation — Springs'.

Part 1 Simplified representation

Part 2 Presentation of data for cylindrical helical compression springs

Part 3 Vocabulary

In view of the above, the committee responsible for the formulation of this standard has also decided to revise IS 10716 : 1983 splitting into three parts by adopting the above three parts of ISO 2162 respectively.

This standard (Part 2) establishes a uniform system for the presentation of data and for the representation of cylindrical helical compression springs to be used in technical product documentation. Other parts of this series are given as follows:

IS 10716 (Part 1) : 1999 Technical product documentation — Springs : Part 1 Simplified representation (*first revision*)

IS 10716 (Part 3) : 1999 Technical product documentation — Springs : Part 3 Vocabulary

The text of ISO has been approved as suitable for publication as Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is especially drawn to the following:

Wherever the words, 'International Standard' appear, referring to this standard, they should be read as 'Indian Standard'.

In this adopted standard, reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standards which are to be substituted in their place are listed below along with their degree of equivalence for the editions indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 2162-1 : 1993	IS 10716 (Part 1) : 1999 Technical product documentation — Springs : Part 1 Simplified representation (<i>first revision</i>)	Identical
ISO 2162-3 : 1993	IS 10716 (Part 3) : 1999 Technical product documentation — Springs : Part 3 Vocabulary	do

Indian Standard

TECHNICAL PRODUCT DOCUMENTATION — SPRINGS

PART 2 PRESENTATION OF DATA FOR CYLINDRICAL HELICAL COMPRESSION SPRINGS

1 Scope

This part of ISO 2162 establishes a uniform system for the presentation of technical data and for the representation of cylindrical helical compression springs to be used in technical product documentation intended for e.g. tender and/or order drawings.

2 Normative references

The following standards contain provisions which through reference in this text, constitute provisions of this part of ISO 2162. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this part of ISO 2162 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2162-1:1993, *Technical product documentation — Springs — Part 1: Simplified representation*.

ISO 2162-3:1993, *Technical product documentation — Springs — Part 3: Vocabulary*.

3 Definitions

For the purposes of this part of ISO 2162, the definitions given in ISO 2162-3 apply.

4 Letter symbols

See table 1.

5 Presentation of data

5.1 General

The data presented shall comprise

- a) graphical representation, information on action and on the type of finish to ends; and
- b) design and manufacturing data.

5.2 Representation, data on the spring action and indication of the type of spring ends

Graphical representation of the spring shall be in accordance with ISO 2162-1.

Data on the spring action shall be indicated preferably by means of a load deflection chart (or graph) showing the predominant requirements necessary for the functioning of the spring together with any additional requirements.

The type of spring ends shall be indicated in accordance with table 2.

5.3 Technical data list

The technical data list presented shall include all information necessary for the manufacture of the springs. Possibilities for the adaptation of a certain spring to given requirements during manufacture shall be specified.

In particular, for springs working on a rod the minimum inside diameter of the coil shall be stated, and for springs working in a cylinder the maximum outside diameter of the coil shall be stated.

To aid economy in manufacture, tolerances on sizes should not be unnecessarily restrictive.













An example of a preprinted data list is given in annex A. This form provides a uniform scheme for the presentation and indication of data on helical compression springs, regardless of the method of data entry. It should be used for enquiries, offers and orders for this type of spring.

Table 1 — Spring design parameters and letter symbols

No.	Parameter	Unit	Letter symbol (Formula)
1	outside (external) diameter of spring	mm	D_e
2	enlargement of outside diameter of spring when loaded	mm	ΔD_e
3	inside diameter of spring	mm	D_i
4	mean diameter of coil	mm	$D \left(= \frac{D_e + D_i}{2} \right)$
5	diameter of wire (or bar)	mm	d
6	maximum outside diameter of wire (or bar)	mm	d_{\max}
7	modulus of elasticity (or Young modulus)	N/mm ² or MPa	E
8.1	load cycle frequency	Hz or s ⁻¹	f
8.2	natural frequency (both ends fixed)	Hz or s ⁻¹	f_e
9	spring load for the spring lengths $L_1, L_2, L_3, \dots, L_n$ (at ambient temperature of 20 °C)	N	$F_1, F_2, F_3, \dots, F_n$
10	spring load for the minimum test length L_n	N	F_n
11	theoretical spring load at solid length L_c	N	$F_{c\text{th}}$
12	spring load at temperatures other than 20 °C, e.g. spring load F_2 at 0 °C	N	$F_{2/0}$
13	modulus of rigidity	N/mm ² or MPa	G
14	stress correction factor depending on D/d	—	k
15	free length	mm	L_0
16	spring length for the loads $F_1, F_2, F_3, \dots, F_n$	mm	$L_1, L_2, L_3, \dots, L_n$

No.	Parameter	Unit	Letter symbol (Formula)
17	minimum acceptable test length for F_n	mm	L_n
18	solid length	mm	L_c
19	active coils	—	n
20	total number of coils	—	n_t
21	static axial spring rate	N/mm	R_s
22	static transverse spring rate	N/mm	R_{tr}
23	lateral deflection force at defined axial force	N	ϕC
24	deflection of spring (stroke) between two loads	mm	s_h
25	torsion stress for $F_1, F_2, F_3, \dots, F_n$	N/mm ²	$\tau_1, \tau_2, \dots, \tau_n$
26	torsion stress for L_c	N/mm ²	τ_c
27	torsion stress range (corrected) for $F_1, F_2, F_3, \dots, F_n$	N/mm ²	$\tau_{k1}, \tau_{k2}, \dots, \tau_{kn}$
28	torsion stress (corrected) for a given stroke s_h	N/mm ²	τ_{kh}
29	working temperature (minimum/maximum)	°C	T
30	static axial flexibility	(N/mm) ⁻¹	$1/R_s$
31	static transverse flexibility	(N/mm) ⁻¹	$1/R_t$
32	working or test duration (during relaxation tests)	h	t
33	(required) total number of cycles up to rupture	—	N
34	permissible relaxation at defined initial stress (normally τ_2), temperature and duration	N/mm ²	δF

Table 2 — Types of spring ends

Form	Execution	View	
A	open, not ground		
B	closed, not ground		
C	open, ground		
D	closed, ground		
E	closed, pigtail ends		
F	closed and bent to the centre		

NOTE — The views show a right-hand (RH) spring. However, the same types of ends apply equally for left-hand (LH) springs.


Annex A

(informative)

Example of the presentation of a preprinted data set for a spring

NOTE 1 The actual size of data sheets is A4, in accordance with ISO 5457.

A.1 Front side, or page 1



Title block
(see ISO 7200)

A.2 Overleaf, or page 2

d mm	F_1 \pm N	s_h mm
D mm	L_1 mm	τ_{kh} N/mm ²
D_e \pm mm	τ_1 N/mm ²	k —
D_i \pm mm	τ_{k1} N/mm ²	N	\geq —
L_0 \pm mm	F_2 \pm N	δF	\leq N/mm ²
n —	L_2 mm	f_e Hz
n_t —	τ_2 N/mm ²	R_s N/mm
L_c mm	τ_{k2} N/mm ²	l h
F_{cth} N	F_n N	$T^{1)}$ / °C
τ_c N/mm ²	L_n mm		
		τ_n N/mm ²		
		τ_{kn} N/mm ²		

Direction of helix	LH RH	<input type="radio"/> ²⁾ <input type="radio"/>	Adaptation of the spring	
			Given requirements	Permissible deviations ³⁾
Load cycle frequency, f	static	<input type="radio"/>	<input type="radio"/> One load F_1 , corresponding length L_1 and spring rate R_s	L_0, d, n_t
	dynamic (time limited)	<input type="radio"/>		
	dynamic (time unlimited)	<input type="radio"/>		
Material	G : N/mm ² E : N/mm ²		<input type="radio"/> Two loads F_1/F_2 and corresponding lengths L_1/L_2	L_0, d, n_t
Surface condition	drawn	<input type="radio"/>		
	rolled	<input type="radio"/>		
	machined	<input type="radio"/>		
	shot-peening	<input type="radio"/>		
	free of burr	<input type="radio"/>	<input type="radio"/> Length of the unpreset spring and spring rate R_s	d, n_t
Protective surface coating	— inside	<input type="radio"/>		
	— outside	<input type="radio"/>	<input type="radio"/> One load F_1 and the load of the preset spring	L_0
Degree of presetting, or presetting load				
			<input type="radio"/> One load F_1 , the length of the preset spring and the length of the unpreset spring L_0	n_t, d or n_t, D_e, D_i

Further details, e.g. on surface conditions or tolerances

- 1) Minimum/maximum.
2) ☐ Mark where applicable.
3) The listed parameters may be altered in order to meet the given requirements.

Annex B

(informative)

Bibliography

- [1] ISO 5457:1980, *Technical drawings — Sizes and layout of drawing sheets.*
- [2] ISO 7200:1984, *Technical drawings — Title blocks.*

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards : Monthly Additions'.

This Indian Standard has been developed from Doc : No. LM 02 (0473).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 323 01 31, 323 94 02, 323 33 75

Telegrams: Manaksanstha
(Common to
all offices)

Regional Offices:

Telephone

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110002

{ 323 76 17
323 38 41

Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola
CALCUTTA 700054

{ 337 84 99, 337 85 61
337 86 26, 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022

{ 60 38 43
60 20 25

Southern : C. I. T. Campus, IV Cross Road, CHENNAI 600113

{ 235 02 16, 235 04 42
235 15 19, 235 23 15

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)
MUMBAI 400093

{ 832 92 95, 832 78 58
832 78 91, 832 78 92

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.
COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR.
KANPUR. LUCKNOW. NAGPUR. PATNA. PUNE. THIRUVANANTHAPURAM.